

General Data-Ceiling Cassette

MODEL TKM			200B4D	300B4D	400B4D	500B4D(A)	500B4D(B)	600B4D	800B4D	1000B4D	1200B4D	1400B4D
Air Flow	H	m ³ /h	360	510	680	820	850	1020	1360	1700	2040	2380
	M		280	420	560	630	650	780	1050	1310	1570	1830
	L		200	350	460	500	520	600	800	1010	1210	1410
Cooling Capacity	H	W	2000	2710	3620	4300	4530	5440	7200	9100	10500	12500
	M		1700	2410	3100	3530	3830	4485	6000	7050	8560	10550
	L		1500	2140	2750	3010	3360	3500	3500	5500	6710	8450
Sensible Cooling Capacity	H	W	1430	1672	2600	3020	3340	3960	5450	6160	7260	7970
	M		1250	1500	2260	2510	2900	3100	4186	5200	6190	6770
	L		1130	1400	2090	2140	2460	2735	3832	4380	5210	5760
Heating Capacity	H	W	3000	4070	5440	6450	6800	8160	10800	13700	16000	18800
	M		2480	3520	4650	5320	5750	6700	9350	10600	13700	15260
	L		2190	3150	4130	4510	5100	5200	7690	8300	11200	12700
Noise Level		dB(A)	37	39	41	43	43	45	46	48	50	52
Power Supply			220~240V/1P/50HZ									
Power Input Water Pressure Weight	W		35	45	70	80	80	90	120	150	200	226
	kPa		15	18	25	30	32	37	40	40	40	50
	kg		25	25	26	26	34	34	36	50	50	50
Dimension	L	mm	570				730			930		
	W	mm	570				730			930		
	H	mm	250		290		290			290		
Panel Dimension		mm	650*650*28				850*850*28			1050*1050*28		
Control Method			remote controller or wiring controller									
Cond. Pipe		mm	Φ20									
Connection Method			SOCKET									
Water Connection	In	inch	Rc3/4"									
	Out	inch	Rc3/4"									